

TECHNICAL DATA SHEET

The Luxurious African Collection

CHARACTERISTICS	STANDARDS	RESULT
Dimension (length x width)		1525mm x 229mm
Total thickness		7mm
SPC core		5mm
Wear layer		0.5mm
Underlay		1.5mm IXPE
Warranty		Residential 20 Years* Commercial 5 Years*
Peel resistance	EN431	≥60N
Dimensional stability after exposure to heat	EN434	X Direction ≤0.1% (80°C/6H) Y Direction ≤0.1% (80°C/6H)
Curling after exposure to heat	Refer to ISO 23999:2008	≤1.0mm (80°C/6H)
Squareness	ISO 24342:2007	X Direction: 0mm~+0.1mm Y Direction: 0mm~+0.1mm
Residual indentation	ISO 24343-1:2007	≤0.1mm
Castor chair resistance	EN 425	Type W
Colour fastness to light	ISO 105- B02:2014; Method 3	After standard 6 grade bluewool: 6
Burning - cigarette Test	EN 1399:1997 Method B	Rating 5: No visible change
Stain resistance	ISO 26987:2008	Index 0: Not affected
Slip resistance	DIN 51130 EN 13893	R10 DS
Wear resistance	EN 660-2	Group: T
Fire rating	EN 14041:2004/AC: 2006 EN 13501-1:2007+A1:2009	Bfl-s1
Use standard	EN ISO 10582	32 33

FEATURES & BENEFITS



The water-resistant core made of limestone and polyvinyl chloride



An innovative transparent wear layer for enhanced protection



The unique Click-Lock System for easy, quick and lasting installations



Made using an environmentally conscious manufacturing process



An additional transparent UV resistance layer for longer lasting performance



The wood grain embossed finish for a natural feel underfoot



A pre-attached underlay for cushioning and superior acoustic comfort



Residential 15 Years*
Commercial 3 Years*

*Terms and conditions apply